

# ZIP100- and Floppy-drive

	FZ110A	FD1231H
Capacity	100 MByte	1,44/0,72 MByte
Data transfer rate	up to 1,4 MByte/s	125/250 KByte/s
Track/Track access		3 ms
Spindle speed		300 U/min
Average access time	29 ms	94 ms
Average start/stop time	3 sec	0,5 sec
Sort format time	10 sec	
MTBF	100.000 hours	30.000 hours
Voltage	5 V	5 V
Power consumption		
Stand by		0,015 W
Read/Write		1,4 W
Interface	IDE-ATAPI	Floppy
Dimensions (w x h x d)	101,4 x 25,4 x 163,6 mm	101,6 x 25,4 x 146 mm
Weight	ca. 0,388 kg	ca. 0,430 kg
Disks		3,5" double-side high density 3,5" double-sided density

The specification is subject to change without notice.

## FZ110A

- Expand HDD capacity with out limit by 100 MB a time.
- Low access time only 29 ms.
- IDE-ATAPI interface
- Bootability
- Operating systems: Windows 95, Windows NT, Windows 3.1, DOS
- ZIP TOOL Software on CD-ROM Media
- Driver software WIN 3,1, WIN 95, WIN-NT, DOS on 3,5" Floppy
- Manual

## FD1231H

- Advanced LSI Technology
- 25,4 mm height
- Low power consumption
- Low noise



NEC Deutschland GmbH  
Steinheilstr. 4-6  
D-85737 Ismaning

Deutschland  
24-Stunden-Info-Telefon:  
0180/5 24 25 21  
(DM 0,24/Minute)

Österreich/Schweiz  
+49-89-9 62 74-0

Internet: [www.necd.de](http://www.necd.de)

**NEC**  
One idea ahead.